

01  
at  
Contd

a plurality of attachment components adapted to be assembled into a plurality of attachment means each of a different configuration for attaching said shaft holder to the surface, at least one of said attachment means comprising the assembly of less than all of said plurality of attachment components.

Sub  
E2 7

50. (Amended) A system for mounting a device to a surface using one of a plurality of devices each of a different configuration that can be assembled from the system, the system comprising:

C2

a shaft holder having a plurality of walls, a bottom having a first hole formed therein, and an open top so as to form a receptacle for receiving the device, wherein the device is removably insertable into said receptacle;

a plurality of threaded rods;

a nut;

a clamping plate having a second hole centrally located therein;

a first member having a first flange and a second flange generally perpendicularly attached to said first flange, said first flange having a third hole formed therein, and said second flange having at least a fourth hole formed therein; and

a second member having a third flange and a fourth flange generally perpendicularly attached to said third flange, said third flange having a fifth hole formed therein, and said fourth flange having at least a sixth hole formed therein; said shaft holder, said plurality of threaded rods, said nut, said clamping plate, said first member and said second member comprising attachment components adapted to be assembled into said plurality of devices, at least one of said plurality of devices comprising the assembly of less than all of said attachment components provided that all of said plurality of devices at least includes said shaft holder.

*D27* 63. (Amended) An apparatus of mounting a device to a supporting surface, the apparatus comprising:

*C3* a shaft holder including a bottom having a first hole formed therein and an open top forming a receptacle therein for receiving the device, wherein the device is removably positionable within said shaft holder;

a threaded rod positioned to extend through said first hole;

a nut in threaded engagement with said threaded rod; and a plurality of attachment components adapted to be assembled into a plurality of attachment means each of a different configuration for attaching said shaft holder to the surface, at least one of said attachment means comprising the assembly of less than all of said plurality of attachment components.

*D37* 67. (Amended) A system for mounting a device to a supporting surface using one of a plurality of devices each of a different configuration that can be assembled from the system, the system comprising:

*C4* a shaft holder including a bottom having a first hole formed therein and an open top forming a receptacle for receiving the device, wherein the device is removably insertable into said receptacle;

a plurality of threaded rods;

a nut;

a first member having a first flange and a second flange generally perpendicularly attached to said first flange, said first flange having a second hole formed therein, and said second flange having at least a third hole formed therein; and a second member having a third flange and a fourth flange generally perpendicularly attached to said third flange, said third flange having a fourth hole formed therein, and said fourth flange having at least a fifth hole formed therein; said shaft holder, said plurality of threaded rods, said nut, said clamping

D3  
C4  
Contd

plate, said first member and said second member comprising attachment components adapted to be assembled into said plurality of devices, at least one of said plurality of devices comprising the assembly of less than all of said attachment components provided that all of said plurality of devices at least includes said shaft holder.

Insert new claims 72-73 as follows:

CB

Sub 72. (New) An apparatus of mounting a device to a supporting surface, the apparatus comprising:

a shaft holder including a bottom and an open top forming a receptacle therein for receiving the device, wherein the device is removably positionable within said shaft holder;

a threaded rod positioned to extend from said bottom surface of said shaft holder; and

a plurality of attachment components adapted to be assembled into a plurality of attachment means each of a different configuration for attaching said shaft holder to the surface, at least one of said attachment means comprising the assembly of less than all of said plurality of attachment components.

73. (New) The apparatus of claim 72, wherein at least one of said plurality of attachment components is attached to said threaded rod.